



COMPANY | CONTACT PERSON

DELIVERY ADDRESS

REFERENCE

DELIVERY DATE

TSE Trailer System Engineering
GmbH & Co. KG
Bei der Mühle 4
D-72365 Ratshausen

Tel: +49 7427 92 33 0
Fax: +49 7427 92 33 75
Mail: verkauf@tse-trailersystems.de

CERTIFICATES (MAX. INNER LENGHT)

- WITHOUT CERTIFICATE** (up to 9.980 mm) **beverage VDI 2700 18 t incl. DE9.5**
- Code XL** **18 t** (up to 8.400 mm) **27 t** (semitrailer up to 13.620 mm)
- 12 t PL** (up to 8.400 mm) **14 t PL** (bis 8.400 mm) **tire load** (up to 8.400 mm)
- 18 t PL** (up to 9.400 mm) **27 t PL** (Sattel bis 13.620 mm)

MEASURES (OUTER WIDTH 2.550 MM)

inner length _____ mm

side loading height (inner length – 1800 mm up to 3100 mm, grid 25 mm) _____ mm

ROOFSYSTEM

- sliding roof CS standard 120 mm fixed tarpaulin roof as full tarpaulin roof 115 mm (only with Code XL)
- sliding roof CS mega 185 mm hamburger full tarpaulin roof (without certificate)
- fixed tarpaulin roof CS 115 mm

LIFTING SYSTEM (HEIGHT 400 MM)

- WITHOUT lifting roof central hydro-pneumatical
- central hydraulic "liftmaster" mechanical stanchion lifter *

* from clear side loading height 2.450 mm and with straight front wall reduced clear side loading width (-120 mm)

OPTIONS

- sliding roof to open from the front mounting kit carapax-roof tarpaulin
- liftable with closed doors (only for CS-Mega) stanchion adapter (+ 50 mm only for CS Mega)

SIDE VERSIONS

LEFT SIDE

RIGHT SIDE

- | | | |
|--|--------------------------|--------------------------|
| Curtainsider/full tarpaulin roof (middle stanchions according to selected certificate) | <input type="checkbox"/> | <input type="checkbox"/> |
| - variant: battenless construction (Code XL) with front wall semitrailer and steel corner stanchions, also with rear load securing (tarpaulin then necessarily supplied by TSE) | <input type="checkbox"/> | <input type="checkbox"/> |
| Dropsides (dto., prepared for the connection of drop sides) | <input type="checkbox"/> | <input type="checkbox"/> |
| Quickcurtainsider (incl. micro-stanchions made of steel, 2 x guide carriages, pallet stop) | <input type="checkbox"/> | <input type="checkbox"/> |
| <input type="checkbox"/> option: quick lock device <input type="radio"/> front <input type="radio"/> rear (only for alu doors) | | |
| <input type="checkbox"/> middle stanchions (1 pair up to 7.700 mm, 2 pair up to 8.225 mm, above that 3 pair) | | pair |
| <input type="checkbox"/> aluminum slats (v-shape) (specify number/fixed length: 2.426, 3.300, 3.850, 4.700 mm) | pieces | mm |
| <input type="checkbox"/> drop sides TSE (heights 400 up to 1000 mm, see extra sheet) | | |
| <input type="checkbox"/> tarpaulin (see extra sheet) | | |



FRONT WALL

- straight, aluminum** (truck & trailer, overlap 52 mm)
- straight with tarpaulin tension, aluminum** (truck & trailer, incl. ratchet spanner overlap 82 mm)
- cranked, aluminum** (semitrailer)
- cranked, aluminum with steel stanchions** (hot-tip galvanised, semitrailer)
- load-through-portal** (Front portal as per selection Rear portal)

OPTIONS

- lashing rail inside** (all front walls, see extra sheet to define the height)
- front wall stanchion additionally with payload 12 t or 14 t**
- quick release device** (front wall semitrailer, steel)
- tarpaulin tensioning for semitrailer frontwall (steel) - for 120 mm frame height**

REAR PORTAL

- aluminum doors 2-panel, 37 mm alu-stanchions**
- aluminium doors 2-panel, 35 mm steel-stanchions** (hot-tip galvanised)
- aluminum doors 4-panel, 37mm alu-stanchions**
- aluminium doors 4-panel, 35 mm steel-stanchions** (hot-tip galvanised)
- stanchions for taillift, 50 mm, alu, clear width 2450 mm** (taillift-width 2490 mm) (liftable only hydraulically)
- stanchions for taillift, 35 mm, steel, clear width 2480 mm** (taillift-width 2520 mm) (hot-tip galvanised)

OPTIONS

- double-jointed hinge 270°** (rear- and load-through portal, can also be retrofitted for existing doors TSE and SCB)
- integrated (recessed) door locks** (rearside and Code XL only)
- extended door panel: top _____ mm bottom _____ mm** (rear- and load-through portal)
- top flap: height taillift from top edge of floor _____ mm** (check supplementary sheet)
- rear dropside** (only for stanchions for taillift, 35 mm, steel)

height: 600 mm 700 mm

SURFACE

- aluminium anodized**
- aluminium natural**
- powder coated** (RAL colour) _____

COMMENTS