

SUPPLEMENT TARPAULIN

v2024/01



COMPANY | CONTACT PERSON

DELIVERY ADDRESS

REFERENCE

DELIVERY DATE

TSE Trailer System Engineering GmbH & Co. KG
Bei der Mühle 4
D-72365 Ratshausen

Tel: +49 7427 92 33 0
Fax: +49 7427 92 33 75
Mail: verkauf@tse-trailersystems.de

DESCRIPTION SCOPE OF DELIVERY SPECIFICATION

Quality tarpaulins made of coated high-strength polyester fabrics, which are manufactured with a special surface finish for the high demands of the commercial vehicle sector and have the necessary load-bearing capacity.

Tarpaulin fabric	The Panama fabric used complies with the load securing standard DIN EN 12641-2 Colour variation in almost all common RAL shades. Further colours on request
Weld-on belts	Number of horizontal belts according to load securing standard DIN EN 12641-2 Vertical belts according to number of tensioners/rollers Strap with 2400 daN breaking load for the vertical straps + the lowest horizontal strap Strap with 1300 daN breaking load for the top 3 horizontal straps (if the vehicle height allows 4 horizontal straps), strap colour: dark grey, width: 48 mm
Tarpaulin tensioner/ Buckles, Strap and hook	Stainless steel tilt safety tensioner with brake, without logo Tensioner spacing in accordance with load securing standard DIN EN 12641-2 1 hook per tensioner set for securing the tarpaulin to the vehicle Tarpaulin tensioner strap with 2700 daN breaking strength, colour: silver-grey, width: 45 mm
Tarpaulin roller	Integrated tarpaulin rollers TSE-ID 645435 (CS) oder 645320 (MEGA)
Handle	Handles mounted on the front and rear of the tarpaulin
Contour marking	Side contour marking Design always stripes + corners, without logo Colour: white (standard) On request: yellow, red
Theft/cut protection	Reinforcement by a firmly connected steel wire construction in a 150 x 150 mm grid Steel wire rope with a diameter of 1.5 mm encased in a grey PVC reinforcement strip
Load securing tarpaulins for battenless bodies	Aramid fibre belts are used instead of the usual weld-on belts. The "battenless design" is based on 3 rows per side. With 21 loops per row (based on a trailer length of 13.60 m). Always in conjunction with the "anti-theft / cut protection" option.
Digital printing/Labeling	A specially developed top-coat protects the printed image from external influences and significantly reduces soiling behaviour. Please note our data requirements.

DIMENSIONS

made to match the kit (120mm TSE subframe) deviating height (+/-) _____ mm

SCOPE OF DELIVERY

Roof tarpaulin (standard) Side tarpaulin left (standard) Side tarpaulin right (standard)

OPTIONS

- Carapax reinforcement according to DIN EN12642 XL (for roof tarpaulin) Theft/cut protection (for side tarpaulin left/right)
 Load securing tarpaulins for battenless bodies (includes Theft- /cut protection) Quick Curtainsider (Plank tarpaulins)

SURFACE

- Colouring (RAL-shade specified) _____
 Digital printing (for almost any motif, please note data requirements)
 Labelling (as high-quality screen print or individual motif, please note data requirements)

COMMENTS

DATE, SIGNATURE